TUREK TIRE

TK118

Apply for steer and trailer wheel position of standard load trucks on high-speed road and good road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	14.5	149/146	18	L	8.25
11R24.5	14.5	152/149	18	L	8.25
295/75R22.5	14.5	146/143	16	L	9.00
295/80R22.5	14.5	152/149	18	L	9.00
315/80R22.5	14.5	157/154	20	L	9.00

TK201

Apply for all wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	14.5	149/146	18	L	8.25
11R24.5	14.5	152/149	18	K	8.25
13R22.5	15	156/153	20	K	9.75
12.00R24	15	160/157	20	K	8.5
315/80R22.5	14.5	157/154	20	K	9.00
7.50R16	12	125/121	16	K	6.00G
8.25R16	14	128/124	16	K	6.50H
8.25R20	14	139/137	16	K	6.5
9.00R20	14	144/142	16	K	7.0
10.00R20	14	149/146	18	K	7.5
11.00R20	15	152/149	18	K	8.0
12.00R20	15	154/151	18	K	8.5
12R22.5	15	152/149	18	L	9.00

TK208



Apply for all wheel position of heavy duty trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
13R22.5	17.5	156/153	20	K	9.75
315/80R22.5	14.5	157/154	20	K	9.00
7.50R16	15	125/121	16	K	6.00G
8.25R16	15	128/124	16	K	6.50H
8.25R20	18.5	139/137	16	K	6.5
9.00R20	18.5	144/142	16	K	7.0
10.00R20	18.5	149/146	18	K	7.5
11.00R20	16.5	152/149	18	K	8.0
12.00R20	17.5	156/153	20	K	8.5
12R22.5	17.5	152/149	18	L	9.00

TK198



Apply for driving wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
295/80R22.5	20	152/149	18	L	9.00

TK228

Apply for driving and trailer wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	20	149/146	18	K	8.25
11R24.5	20	152/149	18	K	8.25
295/75R22.5	20	146/143	16	K	9.00

TK311

Apply for driving and trailer wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	23.5	152/149	18	K	9.00
315/80R22.5	19	157/154	20	K	9.00

TK320

Apply for driving wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	20	149/146	18	K	8.25
12.00R24	20	160/157	20	L	8.5
295/80R22.5	20	152/149	18	K	9.00



TK117

Apply for all wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	14.5	149/146	18	L	8.25



TK155

Apply for trailer wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
385/65R22.5	15.5	160	20	L	11.75



TK166

Apply for trailer wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
385/65R22.5	15	160	20	L	11.75



TK308

Apply for driving and trailer wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	21.5	149/146	18	K	8.25



TK218

Apply for all wheel position of heavy duty trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
13R22.5	16.5	156/153	20	K	9.75



TK101

Apply for steer and trailer wheel position of standard load trucks on good road and high-speed road with medium and long-distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	15	152/149	18	L	9.00



TK292

Apply for trailer wheel position of standard load trucks on high-speed road and good road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	15	152/149	18	K	9.00



TK106

Apply for trailer wheel position of standard load trucks on high-speed road and good road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
7.00R16	13.5	118/114	14	L	5.50F
7.50R16	15	125/121	16	K	6.00G
8.25R16	15	128/124	16	K	6.50H
12R22.5	16.5	152/149	18	L	9.00



TK206

Apply for trailer wheel position of standard load trucks on high-speed road and good road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	16.5	152/149	18	L	9.00

TK259

Apply for trailer wheel position of standard load trucks on high-speed road and good road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	16.5	152/149	18	L	9.00



TK310

Apply for driving and trailer wheel position of standard load trucks on good road and paved road with short and medium distances.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	19	152/149	18	K	9.00



TK312

Apply for driving and trailer wheel position of standard load trucks on good road, paved road with medium and short distance standard.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	19	152/149	18	K	9.00



TK199

Apply for driving wheel of standard load trucks with short and medium distances on good road and high-speed road.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK188

Apply for driving wheel position of standard load trucks with short and medium distances on good road and high-speed road.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK313

Apply for driving and trailer wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	K	9.00



TK108

Apply for all wheel position of heavy duty trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK255

Apply for all wheel position of heavy duty trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK196

Apply for driving wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK322

Apply for driving and trailer wheel position of standard load trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	23.5	152/149	18	K	9.00

TK256

Apply for all wheel position of heavy duty trucks on good road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	17.5	152/149	18	L	9.00



TK211

Apply for all wheel position of standard load light trucks and buses with short and medium distance on good road and paved road.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
7.00R16	13.5	118/114	14	L	5.50F



TK301

Apply for driving wheel position of standard load trucks on paved road and mixed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
8.25R20	20	139/137	16	K	6.5
9.00R20	20	144/142	16	K	7.0
10.00R20	20	149/146	18	K	7.5
11.00R20	18.5	152/149	18	K	8.0
12.00R20	18.5	154/151	18	K	8.5



TK302

Apply for all wheel position of standard load light trucks on paved road and mixed road with medium and short distance.



Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
7.00R16	18	118/114	14	K	5.50F
7.50R16	18.5	125/121	16	K	6.00G
8.25R16	18.5	128/124	16	K	6.50H
12.00R20	18.5	158/155	22	K	8.5

TK305

Apply for driving wheel position of heavy duty trucks on paved road and mixed road with medium and short distance.



Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
10.00R20	19.5	149/146	18	K	7.5
11.00R20	18	152/149	18	K	8.0
12.00R20	18	156/153	20	K	8.5

TK309

Apply for driving wheel position of heavy duty trucks on mixed road and paved road with medium and short distance.



Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	20	156/153	20	K	8.5

TK303

Apply for driving wheel position of heavy duty trucks on mixed road and paved road with medium and short distance.



Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11.00R20	20	152/149	18	K	8.0
12.00R20	20	156/153	20	K	8.5
12R22.5	18.5	152/149	18	K	9.00

TK336

Apply for driving wheel position of standard load trucks on paved road and mixed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11.00R20	24	152/149	18	J	8.0
12.00R20	24	154/151	18	K	8.5

TK331

Apply for driving wheel position of standard load trucks on paved road and mixed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
7.00R16	19	118/114	14	J	5.50F
7.50R16	19.5	125/121	16	J	6.00G
8.25R16	19.5	128/124	16	J	6.50H
8.25R20	24	139/137	16	J	6.5
9.00R20	24	144/142	16	J	7.0
10.00R20	24	149/146	18	J	7.5
11.00R20	24	152/149	18	J	8.0
12.00R20	24	156/153	20	J	8.5
12R22.5	24	152/149	18	K	9.00

TK337

Apply for driving wheel position of heavy duty trucks on paved road and mixed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	24	156/153	20	D	8.5

Mixed pavement

Mine pavement

TK332

Apply for driving wheel position of heavy duty trucks on paved road and mixed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11.00R20	24	152/149	18	J	8.0
12.00R20	23	156/153	20	D	8.5

Mixed pavement

Mine pavement

TK330

Apply for driving wheel position of heavy duty trucks on mixed road and paved road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	24	156/153	20	J	8.5

Mixed pavement

Mine pavement

TK360

Apply for driving wheel position of heavy duty trucks on mixed road and paved road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11.00R20	24	152/149	18	F	8.0
12.00R20	24.5	156/153	20	F	8.5

Mixed pavement

Mine pavement

TK103

Apply for trailer wheel position of standard load trucks on good road and high-speed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	16.5	152/149	18	L	9.00



TK126

Apply for all wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	16.5	152/149	18	L	9.00



TK288

Apply for all wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	16.5	152/149	18	L	9.00



TK122

Apply for trailer wheel position of standard load trucks on good road and high-speed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	18.5	152/149	18	L	9.00



TK277

Apply for all wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	18.5	152/149	18	L	9.00



TK128

Apply for trailer wheel position of standard load trucks on good road and high-speed road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11R22.5	18	149/146	18	L	8.25
12R22.5	18	152/149	18	L	9.00
275/80R22.5	18	149/146	18	L	8.25
295/60R22.5	16.5	150/147	18	L	9.00
295/75R22.5	17	152/149	18	L	9.00



TK165

Apply for driving wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20.5	152/149	18	L	9.00



TK167

Apply for driving and trailer wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK168

Apply for driving and trailer wheel position of standard load trucks on good road and high-speed road with medium and long distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12R22.5	20	152/149	18	L	9.00



TK266

Apply for driving wheel position of heavy duty trucks on mixed road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
11.00R20	18.5	152/149	18	K	8.0
12.00R20	20	158/155	22	K	8.5



TK355

Apply for driving wheel position of heavy duty trucks on mixed road and paved road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	22	158/155	22	K	8.5



TK361

Apply for driving wheel position of heavy duty trucks on mixed road and mining area road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	25.5	160/157	24	A8	8.5

TK363

Apply for driving wheel position of heavy duty trucks on mixed road and mining area road with medium and short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	25	160/157	24	D	8.5

Mixed pavement

Mine pavement

TK362

Apply for driving wheel position of heavy duty trucks on mixed road and mining area road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	26.5	160/157	24	A8	8.5

Mixed pavement

Mine pavement

TK365

Apply for driving wheel position of heavy duty trucks on mining area road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	26.5	160/157	24	A8	8.5

Mixed pavement

Mine pavement

TK397

Apply for driving wheel position of heavy duty trucks on mining area road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	29	160/157	24	A8	8.5

Mixed pavement

Mine pavement

TK398

Apply for driving wheel position of heavy duty trucks on mining area road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	33	160/157	24	D	8.5

Mixed pavement

Mine pavement

TK399

Apply for driving wheel position of heavy duty trucks on mining area road with short distance.

Size	Tread Depth (mm)	Load Index Single/Dual	Ply Rating	Speed Symbol	Standard Rim
12.00R20	33	160/157	24	D	8.5

Mixed pavement

Mine pavement